


DANGER! **FLAMMABLE VAPOR. CONTENTS UNDER PRESSURE. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION.**
Read other cautions on side/back panel before using.

¡PELIGRO! **VAPOR INFLAMABLE. CONTENIDO BAJO PRESIÓN. PROVOCA IRRITACIÓN OCULAR, EN LA PIEL Y EN LAS VÍAS RESPIRATORIAS.**
Lea otras precauciones en el panel posterior y lateral antes de usar.

Net Wt 14 OZ
(396 g)

WATER BASED

Homax® Easy Patch Ceiling Texture replicates popcorn, perlite or aggregate-type ceiling textures. Use to patch and repair damaged ceiling texture, or apply new texture to small areas.




Watch a How-to Video at homaxproducts.com or scan this code to watch now!

Ver el Video Instuctivo en homaxproducts.com o explore con su Smartphone para verlo ahora.

PROTECT CARPET, FURNITURE AND WALLS FROM OVERSPRAY.
- Water-based, use warm water for clean up
- Sprays best between 68°-72°F
- Eye protection recommended

DIRECTIONS FOR USE: MAKE ANY NECESSARY CEILING REPAIRS BEFORE APPLYING. USE A PUTTY KNIFE TO SCRAPE AWAY DAMAGED TEXTURE, AND TO SOFTEN HARD EDGES AROUND THE PATCH AREA. WATER DAMAGED OR STAINED AREAS SHOULD BE PRIMED/ SEALED WHITE PRIOR TO USE.

1. Shake can vigorously for 1 full minute AFTER ball starts to rattle.
2. Carefully insert straw into nozzle.
3. Spray a short burst on scrap cardboard or drywall to prepare nozzle.
4. Hold can vertically approximately 18"-24" from ceiling.
5. SPRAY using a sweeping (back and forth) motion and feathering texture into surrounding area. Apply as a splatter, not fully coating surface. Less is better. If a heavier texture is desired, allow first coat to partially dry, then apply a second coat to build texture. Shake can occasionally throughout use.
   DRY TIME: Allow texture to dry 24 hours.
   TIP: In warmer temperatures, apply with a lighter touch to the actuator for the best texture match.
   TIP: Painting is not required, but if desired to match surrounding area, apply lightly with paintbrush or foam pad.
   TO STORE: Turn can upside down and spray until texture is cleared.



PROTEJA LAS ALFOMBRAS, MUEBLES Y PAREDES DEL EXCESO DE ROCIADO.
- A base de agua, utilice agua tibia para la limpieza.
- Se rocía mejor entre 20 °C a 22,2 °C.
- Se recomienda el uso de lentes de protección.

INSTRUCCIONES DE USO: ANTES DE LA APLICACIÓN, REPARE EL TECHO SEGÚN SEA NECESARIO. UTILICE UNA ESPÁTULA PARA MASILLA PARA RASPAR LA TEXTURA DAÑADA Y PARA SUAVIZAR LOS BORDES ENDURECIDOS ALREDOR DEL ÁREA QUE SE VA A RESTAURAR. SE DEBE APLICAR PINTURA BASE/SELLADOR BLANCO A LAS ÁREAS DAÑADAS POR EL AGUA O MANCHADAS ANTES DE USAR.

1. Agite la lata vigorosamente durante un minuto LUEGO de que la bola empiece a hacer ruido.
2. Inserte la pajilla en la boquilla con mucho cuidado.
3. Rocíe un chorro en un cartón o en un panel de yeso para preparar la boquilla.
4. Sostenga la lata de forma vertical a una distancia aproximada de 45,72 cm a 60,96 cm del techo.
5. ROCÍE con un movimiento de barrido (una y otra vez) y con acabado irregular sobre la textura del área circundante. Aplique como si salpicara el producto, sin cubrir completamente la superficie. Si se aplica menos es mejor. Si se desea lograr una textura más densa, deje que la primera capa se seque parcialmente y luego aplique una segunda capa para crear la textura. Agite la lata de vez en cuando mientras la use.

TIEMPO DE SECADO: Deje que la textura seque por 24 horas.
CONSEJO: En temperaturas más cálidas, aplique con un toque ligero al activador para lograr una mejor combinación de textura.
CONSEJO: No se requiere pintar, pero si desea combinar con el área circundante, aplique ligeramente con una brocha o con una almohadilla de espuma.
PARA ALMACENAR: Coloque la lata en posición invertida y rocíe hasta que no quede rastro de textura.

DANGER! FLAMMABLE VAPOR. CONTENTS UNDER PRESSURE. CAUSES EYE, SKIN AND RESPIRATORY TRACT IRRITATION. Contains Calcium Carbonate, Clay, Perlite, Titanium Dioxide and Dimethyl Ether (propellant). Vapors may catch fire. Keep away from heat, sparks and flame. Extinguish all flames and sources of ignition during use and until all vapors are gone. Prevent build-up of vapors by opening all windows and doors to achieve cross-ventilation. Store upright in a cool, dry place. Avoid prolonged exposure to sunlight and other heat sources that may cause bursting. Do not puncture, incinerate, burn or store above 120°F. Use with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with eyes and skin. Wear safety glasses or goggles. Wash hands after using. **FIRST AID:** For eye contact, flush thoroughly with water for 15 minutes and get medical attention. For skin contact, wash thoroughly with soap and water. If inhaled, remove person to fresh air. If breathing does not improve, get medical attention. **KEEP OUT OF THE REACH OF CHILDREN. WARNING:** This product contains a chemical known to the State of California to cause cancer. **WARNING**: If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. Contact the National Lead Information Hotline at 1-800-424-LEAD or log on to www.epa.gov/lead. **ASBESTOS WARNING:** If your ceiling texture was applied prior to 1979, DO NOT attempt to remove it without having it tested for asbestos content. Contact your local EPA office or log on to www.epa.gov/asbestos for information.

Flat Paint Product VOC < 60% MIR <1.20

This product is covered by one or more U.S. Patents.

STEEL

Homax® A Premier Brand of
The Homax Group, Inc.
Bellingham WA 98227
www.homaxproducts.com
800-729-9029
MADE IN USA

4094_32862 041613

